

## FEATURES

- Wattage selectable provides product flexibility
- Tool-free DIP switch for wattage selection
- 0-10V dimmable
- Magnetic embedded for ease of installation
- Optional TEK screws included
- 4-way plug-n-play harness
- UL rated class P

DRIVER SPECIFICATIONS				
WATTAGE	PRODUCT NUMBER	DIMENSIONS (L x W x H)	INPUT VOLTAGE	OUTPUT VOLTAGE
20W	MRK-Driver-20W-Plus	9.21" x 1.43" x 1.15"	100-277V	33-42VDC
30W	MRK-Driver-30W-Plus	9.21" x 1.43" x 1.15"	100-277V	33-42VDC
40W	MRK-Driver-40W-Plus	9.21" x 1.43" x 1.15"	100-277V	33-42VDC
50W	MRK-Driver-50W-Plus	9.21" x 1.43" x 1.15"	100-277V	33-42VDC
60W	MRK-Driver-60W-Plus	9.21" x 1.43" x 1.15"	100-277V	33-42VDC
100W	MRK-Driver-100W-4WH-Plus	13.62" x 1.43" x 1.15"	100-277V	33-42VDC

### Enhanced Product Flexibility

Wattage Selectable options allow the end user to adjust lumen output to their specific needs.

Wattage	Wattage Power Selectable Options	Default Wattage
20W	22W, 20W, 18W, 16W, 14W, 10W, 8W	20W
30W	32W, 30W, 28W, 24W, 20W, 16W, 10W	30W
40W	42W, 40W, 38W, 32W, 30W, 28W, 24W	40W
50W	52W, 50W, 45W, 40W, 38W, 30W, 25W	50W
60W	62W, 60W, 57W, 55W, 50W, 45W, 40W	60W
100W	100W, 95W, 90W, 85W, 75W, 70W, 65W	100W